



# FLEXHAULER

## EMBRACE THE FUTURE OF HAULING

### SPECS

<b>Model</b>	Flex Hauler
<b>Trailer Type</b>	Open Utility Trailer
<b>Overall Dimensions</b>	20 ft (L) × 8.5 ft (W)
<b>Deck Height</b>	18 inches (empty)
<b>GVWR</b>	9,990 lbs
<b>Payload Capacity</b>	6,770 lbs
<b>Trailer Weight</b>	3,220 lbs (empty)
<b>Number of Axles</b>	2
<b>Axle Rating</b>	5,200lbs. Dexter axles
<b>Suspension Type</b>	Leaf Spring
<b>Frame Material</b>	A500 Grade B Structural Powder Coated Steel
<b>Floor Material</b>	2" x 8" Pressure-Treated Wood
<b>Coupler Size</b>	Demco eZ-Latch 2 5/16"-inch Ball
<b>Hitch Type</b>	5 Position Adjustable Height Bumper Pull
<b>Brakes</b>	Electric (both Axles)
<b>Lights</b>	LED DOT-Approved
<b>Tires</b>	ST225/75R15, Load Range E
<b>Battery</b>	12 volt deep cycle (included)
<b>Solar charger</b>	3W Durable PulseTech Solar Panel
<b>Tie-downs</b>	Stake Pockets & Built-in 3/8" 5052 Aluminum
<b>Front jack</b>	EQ Systems hydraulic jack
<b>Lift ramp/Platform</b>	Welded 6061-T6 Aluminum
<b>Scissor lift</b>	EQ Systems Hydraulic scissor lift
<b>Controls</b>	Keyed Power on controls for hydraulics
<b>Loading ramps</b>	Steel (included)
<b>Loading ramp Storage</b>	Located under rear cross member
<b>Spare Tire Mount</b>	No (Spare Tire Optional)